



Simplified industrial dispersions

Lucio Isa and Jan Vermant

Department of Materials, ETH Zürich, CH





Dr. Florence Müller
(Postdoc Caltech)



Pierre Lehéricy
(Defense Sept 2025)



Savannah McGowan
postdoc (since 04.2025)




Lukas Woolley




Gabriele Pagani
(Defense Jan 2026)

Complexity in model systems




- + ability to systematically vary features and interactions
- + thermoreversible gels in particular

Simplified industrial dispersions




yielding




thixotropy


Analytical, structural and rheological methods tailored to interrogate structure



stress deconvolution



4D-imaging




local scale forces (OT/CP-AFM)

outline


- Increased complexity of the building block
- Elastoplastic behaviour
 - Modelling of elastoplasticity
 - Imaging of plastic events
- CP-AFM and Optical Tweezers

parameter space







Remember :
 Rough particle gels delay yielding

- Thermoreversible gel
- Outer diameter: 300 nm
- Octadecyl brush
- In tetradecane
- $\phi = 0.15$





Article I : Single particle / colloidal probe AFM / adhesion and sliding friction




Müller, F. J., Ramakrishna, S.N., Isa, L., & Vermant, J., Langmuir 2025 - <https://pubs.acs.org/doi/full/10.1021/acs.langmuir.4c03602>

article 2 : Synergistic effects of Roughness and Shape?



Muller et al., J Colloid Interface Sci, 2025 <https://www.sciencedirect.com/science/article/pii/S0021979725006587>



Tuning Colloidal Gel Properties: The Influence of Central and Noncentral Forces





Particle aspect ratio :

- **Smooth particle systems**
 - Elasticity is proportional to aspect ratio
 - Increase bending rigidity in the local isotropic clusters
- **Rough particle systems**
 - Homogeneous isotropic network structure
 - Hindering of alignment
 - Gel properties are less dependent on the aspect ratio
- **Decouple elastic modulus and yield stress** through surface roughness
- Increase the **node stiffness** in colloidal gels through aspect ratio and surface roughness

Article 3 : Modelling of there adhesive interaction (with M. Bevan, JHU)




- a. TGA measurement
- b. XPS spectrum
- c. Rheology
- d. Grafting density



Muller et al. manuscript to be submitted.

Article 3 : Modelling of there adhesive interaction (with M. Bevan, JHU)




VdW interaction of dense brushes insufficient to explain AFM results
Force needed to account for chain-chain interactions between octadecyl ligands




- a. Hamaker functions
- b. VdW forces between sphere and wall
- c. Force curves
- d. model versus calculations (approach/sep)

Muller et al. manuscript to be submitted.

ART 4 : Universal Time-to-Failure Scaling in Colloidal Gels




steel
polymer
polymer
polymer
polymer
hydrogen
milk gel
hydrogel



Muller et al. manuscript to be submitted.

parameter space



outline

- Increased complexity of the building block
- Elastoplastic behaviour
 - Modelling of elastoplasticity
 - Imaging of plastic events
- CP-AFM and Optical Tweezers

Projects and goals

Multimode model ●

- Interplay between the activation function and the linear relaxation spectrum
- Use LAOS measurement as test for the model

Tensorial model ●


- Validating the tensorial extension of the model
- Predicting complex flow protocols

Gel sedimentation ●


- Real case application of the model
- Predicting slowing changing “solid” like movement

A typical yield stress fluid

0.5 wt% Carbopol[®]940



$$\sigma = \sigma_y + K\dot{\gamma}^n, \quad \sigma \geq \sigma_y$$



1D EVP model

$$\sigma = G\gamma_e$$


$$\dot{\gamma}_e = \dot{\gamma} - \dot{\gamma}_p$$

$$\dot{\gamma}_p = \frac{\sigma}{\eta(\sigma_{eq})}$$


$$\eta(\sigma_{eq}) = \eta_0 a_\sigma(\sigma_{eq})$$

$$\sigma_{eq} = |\sigma|$$

$$\tau(\sigma_{eq}) = \frac{\eta(\sigma_{eq})}{G} = \frac{\eta_0 a(\sigma_{eq})}{G} = \frac{\eta_0}{G} a_\sigma(\sigma_{eq}) = \tau_0 a_\sigma(\sigma_{eq}),$$



Pagani et al. J. Rheol, 2024





$$\eta_{RE}(\sigma_{eq}) = \eta_0^{RE} \left(\left(\frac{\eta_{01}}{\eta_0^{RE}} \right) \frac{\left(\frac{\sigma_{eq}}{\sigma_{01}} \right)}{\sinh \left(\frac{\sigma_{eq}}{\sigma_{01}} \right)} + \left(\frac{\eta_{02}}{\eta_0^{RE}} \right) \frac{\left(\frac{\sigma_{eq}}{\sigma_0} \right)}{\sinh \left(\frac{\sigma_{eq}}{\sigma_0} \right)} \right) = \eta_0^{RE} a_\sigma^{RE}(\sigma_{eq}),$$

Eyring, H. (1936). Viscosity, plasticity, and diffusion as examples of absolute reaction rates. *The Journal of chemical physics*, 4(4), 283-291.

Bonnecaze, R. T., Khabaz, F., Mohan, L., & Cloitre, M. (2020). Excess entropy scaling for soft particle glasses. *Journal of Rheology*, 64(2), 423-431.

finding the shift function



Pagani, G., Hofmann, M., Govaert, L. E., Tervoort, T.A., & Vermant, J. (2024). No yield stress required: Stress-activated flow in simple yield-stress fluids. *Journal of Rheology*, 68(2), 155-170.

Constitutive model

3D model

$$\sigma^d = G B_e^d$$

$$D_t(\mathbf{B}_e) = (\mathbf{L} - \mathbf{L}_p) \cdot \mathbf{B}_e + \mathbf{B}_e \cdot (\mathbf{L} - \mathbf{L}_p)^T$$

$$\sigma_{eq} = f(\sigma)$$

$$\mathbf{L}_p = \frac{\sigma^d}{2\eta(\sigma_{eq})}$$

$$\eta(\sigma_{eq}) = \eta_0 a_\sigma(\sigma_{eq})$$

\mathbf{L}_p : plastic velocity-gradient tensor

\mathbf{B}_e : isochoric left-Cauchy-Green strain tensor


\mathbf{A}^d : deviatoric part of tensor \mathbf{A}

Objective and thermodynamically admissible tensorial model

Multiple levers to adapt the model to the material studied:

1. **Equivalent stress definition**
2. **Activation functions**
3. **Linear relaxation spectrum**

Parametrization relaxation spectrum



Using the **integral formulation** of the model it is possible to extract of the linear relaxation modulus from a **transient start-up**

Integral shear model


$$\sigma(t) = \int_{-\infty}^t G(\psi - \psi') \dot{\gamma}(t') dt'$$

$$\psi = \int_{-\infty}^t \frac{dt''}{a_{\sigma}(\sigma(t''))} \quad \psi' = \int_{-\infty}^{t'} \frac{dt''}{a_{\sigma}(\sigma(t''))}$$

Van Breemen, J Mechs Phys Solids, 2011

ETH zürich Schapery, Polymer Engineering & Science, 1969

Parametrization relaxation spectrum




Linear relaxation modulus extracted by **transient** response during **Start-Up** experiments

Fractal maxwell liquid (FMM) model explain the behaviour of the material at low frequency

Loss moduli poorly predicted at high frequency indicate an **additional dissipation**

Comparison with different models (TCC)




Three component (TCC) model *Caggioni, J Rheol, 2020*

1. TCC model \longrightarrow Discontinuity

Comparison with different models (TCC, KH)



$\gamma_0 = 300\%$, $\omega = 2\pi$ rad/s



Kinematic Hardening (KH) model *Dimitriou, J Rheol, 2013*

1. TCC model \longrightarrow Discontinuity
2. KH model \longrightarrow Stress overestimation

Conclusion – Multimode model

Simple model for EVP


Modified maxwell model with a stress-activated plastic viscosity

Physic informed model

Linear and non-linear regime can both be expressed as a function of physical knowledge

Intuitive fitting

Model fitting is performed on standard and quick experiments



Projects and goals

Multimode model ●

- Interplay between the activation function and the linear relaxation spectrum
- Use LAOS measurement as test for the model

Tensorial model ●

- Validating the tensorial extension of the model
- Predicting complex flow protocols

Gel sedimentation ●

- Real case application of the model
- Predicting slowing changing “solid” like movement

Constitutive model

3D model

$$\boldsymbol{\sigma}^d = G \mathbf{B}_e^d$$

$$D_t(\mathbf{B}_e) = (\mathbf{L} - \mathbf{L}_p) \cdot \mathbf{B}_e + \mathbf{B}_e \cdot (\mathbf{L} - \mathbf{L}_p)^T$$

$$\sigma_{eq} = f(\boldsymbol{\sigma})$$

$$\mathbf{L}_p = \frac{\boldsymbol{\sigma}^d}{2\eta(\sigma_{eq})}$$

$$\eta(\sigma_{eq}) = \eta_0 a_\sigma(\sigma_{eq})$$

\mathbf{L}_p : plastic velocity gradient tensor

\mathbf{B}_e : isochoric left-Cauchy-Green strain tensor

\mathbf{A}^d : deviatoric part of tensor \mathbf{A}

Tervoort, J Rheol, 1996

Objective and thermodynamically admissible tensorial model

Multiple levers to adapt the model to the material studied:


1. Equivalent stress definition

2. Activation function Pagani, J Rheol, 2024

3. Linear relaxation spectrum


Testing modes

Simple shear



$$\sigma_m = \sigma_{12}$$


$$N_1 = \frac{\sigma_{12}^2}{G}$$




Von-Mises stress

$$\sigma_{VM} = \sqrt{3J_2} = \sigma_z = \sqrt{3}\sigma_{12}$$

Uniaxial compression



$$\sigma_m = \sigma_z = \sigma_{zz} - \sigma_{rr}$$




Engmann, J.NN. Fluid. Mech., 2005

Simple shear

Normal force


- Statistics needed due to the noise during normal force measurements
- Trend captured by the model prediction




Slip control

Slip promotion

- Perfect slip is needed to properly have uniaxial compression
- A polymer coating was developed to increase wall-slip



Uniaxial compression



Von-Mises stress

$$\sigma_{VM} = \sigma_z = \sqrt{3}\sigma_{12}$$

83 Pa	139 Pa	147 Pa



- Uniaxial compression
- Yielding stress captured by the model
 - Carbopol show strain hardening


Conclusion – Multimode model

Slip control

A polymer coating was designed that actively promote slip during mechanical testing

Tensorial model

The testing the model on different deformation protocols show the generalizability to arbitrary flows



Projects and goals

Multimode model ●

- Interplay between the activation function and the linear relaxation spectrum
- Use LAOS measurement as test for the model

Tensorial model ●

- Validating the tensorial extension of the model
- Predicting complex flow protocols


Gel sedimentation ●

- Real case application of the model
- Predicting slowing changing “solid” like movement

Application

Sedimentation of gels

- Bentonite clays due to relevant industrial interest
- Stress field given by gravitational field



Assumption for simplification

Uniaxial compression


$$B_{zz}, \sigma_{zz}$$

$$\alpha(t, z) = \alpha(t)$$

Mass balance $\longrightarrow \phi = \frac{\phi_0}{\alpha}$

Stress controlled deformation

Application



3D model

$$\boldsymbol{\sigma}^d = G \mathbf{B}_e^d$$


$$D_t(\mathbf{B}_e) = (\mathbf{L} - \mathbf{L}_p) \cdot \mathbf{B}_e + \mathbf{B}_e \cdot (\mathbf{L} - \mathbf{L}_p)^T$$

$$\sigma_{eq} = f(\boldsymbol{\sigma})$$

$$\mathbf{L}_p = \frac{\boldsymbol{\sigma}^d}{2\eta(\sigma_{eq})}$$

$$\eta(\sigma_{eq}) = \eta_0 a_\sigma(\sigma_{eq})$$

Application



3D model

$$\boldsymbol{\sigma}^d = G\mathbf{B}_e^d$$

$$D_t(\mathbf{B}_e) = (\mathbf{L} - \mathbf{L}_p) \cdot \mathbf{B}_e + \mathbf{B}_e \cdot (\mathbf{L} - \mathbf{L}_p)^T$$

$$\sigma_{eq} = f(\boldsymbol{\sigma})$$

$$\mathbf{L}_p = \frac{\boldsymbol{\sigma}^d}{2\eta(\sigma_{eq})}$$

$$\eta(\sigma_{eq}) = \eta_0 a_\sigma(\sigma_{eq})$$

Simplified model

$$\sigma_{zz} = f(z)$$


$$\sigma_{eq} = \frac{1}{2}\sigma_{zz}$$

$$\dot{\epsilon}_p = \frac{\sigma_{zz}}{2\eta(\sigma_{eq})}$$

$$\frac{\dot{\alpha}}{\alpha} = \dot{\epsilon}_p$$

$$\frac{H(t)}{H_0} = \alpha(t)$$

Application




Characterization

- Model characterization from “solid” response
- Combination of creep and amplitude sweep

Application

First attempt


- Analytical solution obtained by assuming a constant effective stress
- Parametrization from flow curve



outline




- Increased complexity of the building block
- Elastoplastic behaviour
 - Modelling of elastoplasticity
 - Imaging of plastic events
- CP-AFM and Optical Tweezers

ART 5 : Kinetic Pathways to Gelation and Effects of Flow-Induced Structuring in Depletion Gels (in Spec Issue for W.R. Russel)



Colombo et al. Industrial & Engineering Chemistry Research (2025) <https://pubs.acs.org/doi/full/10.1021/acs.iecr.4c03873>


Rheoconfocal



Experimental setup

Focus-tunable lens
Scan range : 10 μ m
2 VPS with 300 nm z-resolution


Stress-controlled rheometer



High speed fluorescence camera
100 FPS full frame resolution (4MP)

Confocal scanner
1000 FPS full frame


Flow reversal experiment



Colombo et al., Korea-Aust. Rheol. J. **31**, 2019


Microstructure evolution analysis methods

Particle tracking




Adapted Crocker and Grier method for the detection of spherical objects in complex background

U. Gasser et al., Optics Express 2021




Optical flow




Application of 2D Farneback algorithm in each plane followed by reconstruction of the 3D optical flow vectors

G. Farneback, Proceedings of the 13th Scandinavian Conference on Image Analysis, 2003.




Forcing the gels to enter the plastic regime



Using a metric of local plasticity at the particle level

$$D^2(t, \Delta t) = \sum_n \sum_i \left(r_n^i(t) - r_0^i(t) - \sum_j (\delta_{ij} + \varepsilon_{ij}) \times [r_n^j(t - \Delta t) - r_0^j(t - \Delta t)] \right)^2$$

$i, j \in \{x, y, z\}^2 \quad n \in E_N$




Falk and Langer, Phys. Rev. E. **57**, 1998


A closer look at the observable rearrangements

PMMA-g-PHSA depletion gel



$$\phi = 45\%, U_{dep} = -15kT, \dot{\gamma}_{set} = 1.10^{-3}s^{-1}, \dot{\gamma}_{real} = 5 \cdot 10^{-4}s^{-1}$$




Isolation of particles involved in the rearrangement



Coordination analysis shows this rearrangement happen at a weak spot...




...and that the particle move in the vorticity direction




Measuring stress activation curves with optical flow

Applying creep at different stresses



Measuring non-affine zones characteristics with high order motion analysis



$$\hat{A}(t) = \hat{V}(t, t + \Delta t) - \hat{V}(t - \Delta t, t)$$

Non-affine activity at 50 mPa



20%

30%




45%

ϕ

$-14kT$





$-27kT$



$-45kT$

U_{dep}



Non-affine activity zone size distribution at 50 mPa



20%

30%




45%

ϕ



$-14kT$



$-27kT$



$-45kT$




U_{dep}

outline


- Increased complexity of the building block
- Elastoplastic behaviour
 - Modelling of elastoplasticity
 - Imaging of plastic events
- CP-AFM and Optical Tweezers

Rearrangements, configurations, metastability


Interparticle forces




Cluster properties



Formation of spanning network



Rheological properties




Assembly

Thixotropic and aging effects



- Increasing the interparticle **potential**, lowers the **coordination number**.
 - Crowding** with particle needs more material.
- The forces in contact can lead to a difference in aging and shear deformation

➔ Introduce force anisotropy to dictate assembly process


Bending experiments of linear aggregates using OT





Influence of roughness on bending stiffness



Deformation mode in more complex arrangements



Observing failure of structure under tension



Histogram of the yielding events as a function of the bond number in the 13 particles rods.

outline

- ☑ Increased complexity of the building block
- ☑ Elastoplastic behaviour
 - ☑ Modelling of elastoplasticity
 - ☑ Imaging of plastic events
- ☑ CP-AFM and Optical Tweezers